

SILVYN® KLICK-GP



■ Benefits

- Fast assembly
- Easy to disassemble
- High-tensile
- High sealing performance
- Can be rotated

■ Application range

- In combination with protective conduit
- SILVYN® RILL PA6
- SILVYN® RILL PA12
- Robot-building
- Rotating applications

■ Approvals



- UL FILENUMBER E308201

■ Design

- PG connection thread
- Body with inner sealing
- Upper part with snap-in sleeve

■ Note

- For rotating applications, disassemble the upper part to remove sealing, then re-assemble.

■ Suitable conduits

- SILVYN® RILL PA 6 Page 782
- SILVYN® RILL PA 12 Page 783

■ Technical data



Colour delivered
Grey (RAL 7001)
Black (RAL 9005), UV-resistant



Material
PA6



Protection rating
IP 68
IP 69K according to DIN 40050 T.9



Temperature range
-40 °C to +115 °C

Article number	Article designation	Suitable for SILVYN® RILL	For conduit with outer Ø (mm)	Wrench size (mm)	Thread length (mm)	Hole (mm)	Pieces / PU
SILVYN® KLICK-GP grey							
61800860	7	7	10	15.5	10	7	50
61800870	9	9	13	18.0	10	10	50
61800880	11	11	15.8	21.0	10	12.5	50
61800850	13,5	13,5	18.2	24.0	11	13.5	50
61800890	16	16	21.2	27.0	12	17	50
61800900	21	21	28.5	34.0	12	23.5	25
61800910	29	29	34.5	40.0	12	30.5	25
61800920	36	36	42.5	49.0	12	36.5	25
61800930	48	48	54.5	60.0	15	48.5	10
SILVYN® KLICK-GP black							
61800865	7	7	10	15.5	10	7	50
61800875	9	9	13	18.0	10	10	50
61800885	11	11	15.8	21.0	10	12.5	50
61800855	13,5	13,5	18.2	24.0	11	13.5	50
61800895	16	16	21.2	27.0	12	17	50
61800905	21	21	28.5	34.0	12	23.5	25
61800915	29	29	34.5	40.0	12	30.5	25
61800925	36	36	42.5	49.0	12	36.5	25
61800935	48	48	54.5	60.0	15	48.5	10

Photographs are not to scale and do not represent detailed images of the respective products.